

IO 6RTD 6 RTD inputs Modbus Modules Features

These modules are used with HMI, PLC or SCADA via Modbus RTU

protocol. IO Studio is its PC software for setting communication. Data

Acquisition Studio is its PC software for DAQ purpose.

- Portable
- Modbus connectivity
- Simple setup and easy handling
- Up to 128 Module on RS485 network
- Isolated modules available for special applications
- Low-cost IO modules addition to existing PLC system
- Standard software for module configuration and trouble shooting
- Data acquisition software for data storage and Real-time analysis on PC
- IO modules used with the third party softwares via Modbus RTU Protocol
- Interface with field devices to provide real-time data for SCADA / PLC / HMI
- LEDs on every modules for digital IO status, communication and power supply
- Different types of IO Modules AI, AO, DI, DO, RTD, Thermocouples are available
- Direct reading of temperature without scaling by using RTD and Thermocouple Modules

IO 6RTD 6 RTD inputs Modbus Modules Specification

Input	6, RTD Inputs
Type	PT100, Ni 120, PT1000 Ni1000 -DIN, NI1000 Landys & Gyr 10-400 Ohms, 100-4000 Ohms
Connection	2/3 wire
Resolution	0.1 Deg.C
Sample rate	0.52 samples/sec
Drift	100 PPM/Deg.C
Isolation (Field&Logic)	1500 V RMS
Power supply	"+12 V to +24 V"